

nVent ERICO Cadweld Welding Material, Rail F80, Standard



VLASTNOSTI

Mixture consists mainly of copper oxide and aluminum

Primarily used in making connections to load-bearing rail

Welding material is in the top of the tube and starting material is compacted in the bottom of the tube

Packaged by size in plastic tubes with yellow caps

Tubes packaged in plastic boxes along with metal disks

Each welded connection uses a single disk

Non-explosive

Not subject to spontaneous ignition

Meets AREMA® Recommendations; Manual Part 8.1.34, "Recommended Design Criteria for Copper Based Exothermic Welding Material"

See specific nVent ERICO Cadweld connection details to determine welding material requirements

SPECIFIKACE

Katalogové číslo	Article Number
PB115	
PB250	
PB500	163190

DALŠÍ PODROBNOSTI O PRODUKTU

All nVent ERICO Cadweld connections on rail properties must be installed using either nVent ERICO Cadweld Welding Material, Rail F80 or nVent ERICO Cadweld Plus Welding Material, F80.

UPOZORNĚNÍ

Produkty nVent musí být instalovány a používány pouze tak, jak je uvedeno v instrukčních listech a materiálech pro školení nVent. Instrukční listy jsou k dispozici na www.nvent.com a od vašeho zástupce zákaznického servisu nVent. Nesprávná instalace, zneužití, nesprávné použití nebo jiný nedostatek úplného dodržování pokynů a varování nVent může způsobit selhání produktu, poškození majetku, vážné zranění osob a smrt a/nebo zrušit vaši záruku.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Naše portfolio silných značek:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE