

nVent LENTON Interlok HYA15CT Grout Additive, Cold Temperature



The nVent LENTON HYA15LM Grout Additive, Cold Temperature is designed to be used in conjunction with nVent LENTON Interlok grout-fill couplers and nVent LENTON Interlok HY15LM Grout. The additive is used to speed curing and prevent freezing of the grout, thus allowing construction to continue in cold weather. This proprietary grout additive is designed to be used at temperatures between 20 °F and 50 °F (-7 °C and 10 °C).

FUNKTIONER

Allows for cold temperature grouting

Extends the construction season

For use in pump or gravity fill applications

SPECIFIKATIONER

Table 1/1

Katalognummer	Compressive Strength	Working Temperature	Unit Weight
HYA15CT	24.1 MPa @ 1 d, 110.3 MPa @ 28 d	-7 to 10 °C	0.68 kg

YDERLIGERE PRODUKTOPLYSNINGER

For use with HY15LM grout only.

Cold weather concreting procedures, such as ACI 306 Cold Weather Concreting, must be followed.

Prior to installation, please read and understand the detailed instructions and safety notices provided in the nVent LENTON Interlok Instruction Manual.

ADVARSEL

nVent-produkter skal kun installeres og anvendes som angivet i nVents produktvejledninger og træningsmaterialer. Vejledninger er tilgængelige på www.nvent.com og hos din nVent kundeservicerepræsentant. Forkert installation, misbrug, fejlanvendelse eller anden undladelse af fuldt ud at følge nVents instruktioner og advarsler kan medføre funktionsfejl, materielle skader, alvorlige personskader eller død og/eller ugyldiggøre din garanti.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Vores kraftfulde portefølje af mærker:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE