

# **Elexant 650c-Modbus Control Unit**



The nVent RAYCHEM Elexant 650c-Modbus controller is designed for operation with the nVent RAYCHEM heating cables for roof and gutter de-icing and surface snow melting applications.

#### **FEATURES**

Intuitive set-up and programming of the unit with a 4,3" colour touch screen

Flexible temperature control of roof & gutter de-icing and surface snow melting systems

Controls 2 independent heating circuits

Alarm relay with change over contact to signal power, temperature or communication problems

Ambient temperature monitoring with high and low temperature alarm

Offsite configurable - can be set up prior to final installation

DIN rail panel mountable

The Elexant 650c-Modbus is equipped with a RS485 port for Modbus communication to a BMS system which can be used for configuration, monitoring and alarm purposes

Ice rain feature - preheating the surface to prevent the issue of freezing rain (for surface snow melting application only)

## **SPECIFICATIONS**

| Table 1/3         |             |               |                          |        |                   |        |
|-------------------|-------------|---------------|--------------------------|--------|-------------------|--------|
| Catalog<br>Number | Alarm Relay | Communication | Communication s Protocol | Depth  | Hazardous<br>Area | Height |
| 1244-022835       | Yes         | Yes           | Modbus RTU               | 155 mm | No                | 110 mm |

| Table 2/3         |           |          |                      |             |                |                              |
|-------------------|-----------|----------|----------------------|-------------|----------------|------------------------------|
| Catalog<br>Number | IP Rating | Mounting | Output Relay         | Sensor Type | Supply Voltage | Temperature<br>Control Range |
| 1244-022835       | IP20      | DIN Rail | 2 x 4 A @ 230<br>VAC | NTC         | 230 – 253 V    | -20 to 30 °C                 |

| Table 3/3      |       |  |
|----------------|-------|--|
| Catalog Number | Width |  |
| 1244-022835    | 55 mm |  |

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa Tel +32.16.213.511

Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com