

Portable Rail Grinder Grinding Wheel



FEATURES

Used with SBG141 Pedestal Rail Grinder and SBG150 Portable Rail Grinder, Two-Cycle Gas-Powered

Installs easily on the grinder

Enables good control of cleaning operations

Reduction of heat effect

Smooth finish on cleaned surface

For use with various type of surfaces

Helps to eliminate possible resin contamination on the cleaned surface, aiding the nVent ERICO Cadweld process

SPECIFICATIONS

Material: Reinforced Resinoid-Bonded Zirconium

| Table 1/1 | | | |
|----------------|---------|----------|-----------|
| Catalog Number | Beveled | Diameter | Thickness |
| SBS2333 | No | 152.4 mm | 19.05 mm |
| S2129 | Yes | 152.4 mm | 25.4 mm |
| SB22122 | No | 152.4 mm | 25.4 mm |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE