

# Low-Profile Connection Kit for Parallel Heating Cables, Cold-Applied, ATEX



nVent RAYCHEM C-150-E is a cold-applied, low profile, under insulation power connection to flexible power cable, for use with nVent RAYCHEM BTV, QTVR, XTV and KTV. It can be used in applications with temperature ratings from  $-50~\rm ^{\circ}C$  to  $215~\rm ^{\circ}C$ .

# **FEATURES**

Simple and fast to install

Cold-applied: core sealing boot with non-curing sealant; no heat gun, no hot work permit needed

One low profile, under-insulation component for all nVent RAYCHEM industrial self-regulating heating cables

Simplified design in hazardous area, integral part of system approval

Reliable during long life: 10 year extended product warranty available, maintenance free

## **SPECIFICATIONS**

Table 1/2								
Catalog Number	Item Name	Model	Connection Type	Voltage Rating	Current Rating	Max Exposure Temperature		
073704-000	C-150-E	Heating Cable/Connecti on Cable	Cold Applied	277 V	25 A	215 °C		

Table 2/2							
Catalog Number	Item Name	IP Rating	Suitable for Cold Lead				
073704-000	C-150-E	IP66	7.8 – 12.5 mm				

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper

installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific** 

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com **Latin America** 

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com