

Speedway Cable Ladder Flat Elbow, 45°



CERTIFICATIONS



FEATURES

Creates a 45° corner change in cable tray direction

Provides optimal support for high-performance low voltage and data cables

Innovative SPEEDLOK integrated coupling system

Safety edge protects cables during installation

Slotted side channel, eliminating field drilling for cut-to-length applications

IEC 61537 load rating and earthing compliant

Responsive design and layout services, including seismic

SPECIFICATIONS


Finish: Hot-Dip Galvanized

Material: Steel

Table 1/2						
Catalog Number	Article Number	Width (W)	Angle (a)	A	В	С

CL110X150FE4 5HD	840100	150 mm	45 °	326 mm	460 mm	80 mm
CL110X300FE4 5HD	840110	300 mm	45 °	476 mm	566 mm	80 mm
CL110X450FE4 5HD	840120	450 mm	45 °	626 mm	673 mm	80 mm
CL110X600FE4 5HD	840130	600 mm	45 °	776 mm	779 mm	80 mm
CL110X750FE4 5HD	840140	750 mm	45 °	926 mm	885 mm	80 mm
CL110X900FE4 5HD	840150	900 mm	45 °	1076 mm	991 mm	80 mm

Table 2/2						
Catalog Number	Article Number	D				
CL110X150FE45HD	840100	110 mm				
CL110X300FE45HD	840110	110 mm				
CL110X450FE45HD	840120	110 mm				
CL110X600FE45HD	840130	110 mm				
CL110X750FE45HD	840140	110 mm				
CL110X900FE45HD	840150	110 mm				



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

Netherlands: +31 800-0200135 France: +33 800 901 793 Europe

Germany: 800 1890272 Other Countries: +31 13 5835404 APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE

