

Transparent Aluminium Doors, ADA



Components mounted on the enclosure door are protected by the viewing window, but can be easily operated by opening only the viewing window, while the enclosure door can remain closed. The components are protected from the environment and from undesired operations when the viewing window is closed.

FEATURES

Description: Viewing window when used in combination with mounting kit ADAMK. The double-bit 3 mm lock can be replaced by any optional insert or handle. It increases the enclosure depth by 10 mm.

Material: Aluminium and 3 mm acrylic glass.

Finish: Anodised aluminium.

Protection: Complies with IP 54.

Pack quantity: 1 viewing window.

To replace the standard door

Can be used in combination with swing frame, modular chassis or inner door

The double-bit 3 mm lock can be replaced by any optional insert or handle

It increases the enclosures depth by 10 mm (ADA) or 35 mm (ADAB)

Can also be used as a viewing window when used in combination with mounting kit ADAMK/ADABMK

Includes mounting hardware

Number of locks: 1

SPECIFICATIONS

Material: Aluminum

Finish: Mill

Table 1/1						
Catalog Number	Height	Width	Depth	Latch Quantity	Window Size	Number of Locking Devices
ADA03030	300mm	300mm	30mm	1	226 x 226mm	1
ADA04030	400mm	300mm	30mm	1	326 x 226mm	1
ADA04040	400mm	400mm	30mm	1	326 x 326mm	1
ADA04060	400mm	600mm	30mm	1	326 x 526mm	1
ADA05030	500mm	300mm	30mm	1	426 x 226mm	1
ADA05040	500mm	400mm	30mm	1	426 x 326mm	1
ADAB06040	600mm	400mm	30mm	2	522 x 322mm	2
ADAB06060	600mm	600mm	30mm	2	522 x 522mm	2
ADAB06080	600mm	800mm	30mm	2	522 x 722mm	2
ADAB07050	700mm	500mm	30mm	2	622 x 422mm	2
ADAB08060	800mm	600mm	30mm	2	722 x 522mm	2
ADAB10080	1000mm	800mm	30mm	2	922 x 722mm	2
ADAB12060	1200mm	600mm	30mm	2	1122 x 522mm	2
ADAB12080	1200mm	800mm	30mm	2	1122 x 722mm	2

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**