

# **Metal Pressure Clip, Fire-Rated**



#### **CERTIFICATIONS**



#### **FEATURES**

Includes insert for E30 fire rating according to DIN 4102-12

Ideal for smaller runs of cables

Flexible clip retains shape and allows for cables to be inserted after installation

Rounded edges help prevent cable damage

Cables are neatly installed providing a consistent and professional appearance

Low profile allows for installations in tight spaces

#### **SPECIFICATIONS**

Finish: nVent CADDY Armour

Material: Spring Steel

Table 1/1					
Catalog Number	Article Number	Hole Size (HS)	Length (L)		
PKM10H6IN	182048	7.2 mm	171.5mm		

Catalog Number	Article Number	Hole Size (HS)	Length (L)
PKM16H6IN	182049	7.2 mm	233.5mm

# **ADDITIONAL PRODUCT DETAILS**

Fire rating test conducted with cable types listed. Equivalent halogen free safety cable can be used according to national guidelines.

E30 Fire Rating Power Cable Capacity						
Eucasafe (N)HXCH FE 180 E30						
Part Number	Number of Cores	Core Cross Section	Cable Diameter	Number of Cables		
PKM10H6IN	4	1.5 mm²	12.5 mm	8 Max		
	3	1.5 mm²	11.8 mm	8 Max		
	2	1.5 mm²	11.4 mm	8 Max		
PKM16H6IN	4	1.5 mm²	12.5 mm	12 Max		
	3	1.5 mm²	11.8 mm	12 Max		
	2	1.5 mm²	11.4 mm	14 Max		

E30 Fire Rating Data Cable Capacity						
Eucasafe JE-H(St) Bd FE 180 E30						
Part Number	Number of Wire Pairs	Wire Diameter	Cable Diameter	Number of Cables		
PKM10H6IN	2	0.8 mm	6.6 mm	14 Max		
	4	0.8 mm	8.8 mm	10 Max		
PKM16H6IN	2	0.8 mm	6.6 mm	24 Max		
	4	0.8 mm	8.8 mm	18 Max		

## **DIAGRAMS**



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper

installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

# North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

# Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

#### **Europe**

Germany: 800 1890272 Other Countries: +31 13 5835404

#### **APAC**

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

**ERICO** 

**HOFFMAN** 

**ILSCO** 

**SCHROFF** 

**TRACHTE** 



©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.