We connect and protect

Cable Conduits, CON

The cable conduit allows for fast installation of cables while guaranteeing safe and reliable connection between components installed in mobile parts and those in the enclosure.

FEATURES

Description: For flexible and safe protection of cables installed between the door or swing frame and the enclosure's interior. Highly flexible and halogen free.

Material: Polyethylene.

Mounting requirements: Add CONH for direct mounting to profiles.

Pack quantity: 1.

SPECIFICATIONS

Table 1/1						
Catalog Number	**Length**	**Diameter**	**Enclosure Material**	**Product Family**	**Material**	**Finish**
CON16	25000mm	16mm	Mild Steel	Free-Standing	Polyethylene	Smooth
CON29	25000mm	29mm	Mild Steel	Free-Standing	Polyethylene	Smooth
CON36	25000mm	36mm	Mild Steel	Free-Standing	Polyethylene	Smooth
CON48	25000mm	48mm	Mild Steel	Free-Standing	Polyethylene	Smooth

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.