

Stud to Web of Rail Kit



DIAGRAMS



FEATURES

Provides material to directly connect studs to the neutral axis of the rail web utilizing the exothermic process

Kits include an nVent ERICO Cadweld mold allocation, mold cleaning tool, flint ignitor, studs, washers and nuts

SPECIFICATIONS

Number of Connections:	1
Minimum Order Quantity:	50
Material:	Graphite;Silicon Bronze;Stainless Steel 302 (EN 1.4324);Stainless Steel 304 (EN 1.4301)
Rail Type:	RI52;RI59

Table 1/2

Catalog Number	Mold Family	Length (L)	Diameter (Ø)	Thread Size (TS)	Studs	Washers
PBK244	HV	49.27mm	9.5 mm	3/8" UNC	Stainless Steel (1)	3/8" Silicon Bronze Lock Washer (1)
PBK245	HV	49.27mm	18.8 mm	5/8" UNC	Stainless Steel (1)	5/8" Silicon Bronze Lock Washer (1)

Table 2/2


Catalog Number	Nuts
PBK244	3/8"-16 UNC Silicon Bronze Hex Nut (1)
PBK245	5/8"-11 UNC Silicon Bronze Hex Nut (1)

ADDITIONAL PRODUCT DETAILS

Welder frame sold separately.

A gap between conductors may be required. See mold tag for more information.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE