

# nVent CADDY Cat 425 Adjustable Cable Support with BC Beam Clamp



### **CERTIFICATIONS**





# **FEATURES**

Easy installation to beam flanges

Rotates 360 degrees to support various directional runs of cable

Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic

Simple unlocking and locking of bar allows for additional cables to be added easily after installation

Adjustable strap allows for multiple support sizes to reduce inventory

Cost effective alternative to expensive cable tray

cULus® Listed and complies with NEC® and TIA requirements for structured cabling systems

Suitable for air handling spaces (plenum)


# **SPECIFICATIONS**

Table 1/2								
Catalog Number	Material	Finish	Diameter (Ø)	Area	Cable Capacity, Cat 5e	Cable Capacity, Cat 6		

nVent CADDY CAT425BC Steel, Armour, 100 mm, 150 518mm<sup>2</sup> 425 325 Polyethylene Electrogalvaniz mm ed

Table 2/2							
Catalog Number	Cable Capacity, Cat 6A	Flange Thickness (FT)	Static Load				
CAT425BC	210	3.2 - 12.7 mm	450N				

## **DIAGRAMS**



# **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### **North America**

+1.800.753.9221 Option 1 - Customer Care Option 2 - Technical Support

### Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

### Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

# **APAC**

Shanghai: + 86 21 2412 1618/19 Sydney:





Our powerful portfolio of brands:

**CADDY ERICO** 

**HOFFMAN** 

**ILSCO SCHROFF**  **TRACHTE** 

