

ACS-30 User Interface Terminal



nVent RAYCHEM ACS-UIT3 is a user interface terminal used together with the ACS-PCM2-5 panel in the ACS-30 system. With large LCD touch-screen display, it provides easy programming without keyboards or cryptic labels.

FEATURES

Simple to install and operate, with large touch screen display

Alarm outputs

Multiple communications ports (RS-485, RS-232, or 10/100Base-T Ethernet)

BACnet to Modbus protocol gateways, with Modbus registries pre-programmed

USB interface, for easy configuration and firmware upgrades

Reliable during long life: 2 year product warranty available, maintenance free

SPECIFICATIONS

Table 1/2								
Catalog Number	Item Name	Supply Voltage	Display	Material	IP Rating	Height		
10332-039	ACS-UIT3 REPLACEMENT UNIT	10 – 36 V	12" Touch Screen, TFT LCD	FRP	IP20	245 mm		
1244-022626	ACS-30-EU- UIT3	100 – 240 V	12" Touch Screen, TFT LCD	FRP	IP65	400 mm		

Table 2/2							
Catalog Number	Item Name	Width	Depth				
10332-039	ACS-UIT3 REPLACEMENT UNIT	306 mm	63 mm				

Catalog Number	Item Name	Width	Depth
1244-022626	ACS-30-EU-UIT3	400 mm	210 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com