

nVent CADDY Cat HP J-Hook with BC26 Beam Clamp

Data Solutions



CERTIFICATIONS





FEATURES

Easy installation to beam flanges

Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic

Provides superior fill capacity and load rating over most other non-continuous cable support alternatives

Rounded edges on J-Hooks provide proper bend radius support for high performance data cables

Cost effective alternative to expensive cable tray

Complies with EN 50174-2

Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569

SPECIFICATIONS

Material: Steel; Cast Iron

Finish: Pregalvanized; Electrogalvanized

Table 1/2							
Catalog Number	Diameter (Ø)	Area	Cable Capacity, Cat 5e	Cable Capacity, Cat 6	Cable Capacity, Cat 6A	Flange Thickness (FT)	
CAT16HPBC26	25mm	690mm²	20	15	10	21.8mm max	
CAT21HPBC26	33.3mm	1174mm²	50	40	25	21.8mm max	
CAT32HPBC26	50mm	2561mm²	90	60	35	21.8mm max	
CAT48HPBC26	75mm	5974mm²	200	150	80	21.8mm max	


Table 2/2				
Catalog Number	Static Load			
CAT16HPBC26	270N			
CAT21HPBC26	270N			
CAT32HPBC26	270N			
CAT48HPBC26	270N			

ADDITIONAL PRODUCT DETAILS

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.

Cable capacity is calculated based on a 70% fill rate.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper

installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE