

Thermal Compound



FEATURES

- Mineral-filler based heat conducting compound
- Conducts heat from self-regulating heating cables
- Enables additional heat transfer to the rail
- Use is required at field installation of system

SPECIFICATIONS

Table 1/1

Catalog Number	Working Temperature	Unit Weight
RHS4PM8	-46 to 100 °C	0.23 kg
RHS4PC195300	-40 to 200 °C	0.53 kg
RHS4PM1G	-46 to 100 °C	6.62 kg

ADDITIONAL PRODUCT DETAILS

Consult packaging or MSDS for shelf life information.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper

installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE