

# 1 Hole Lug, GL Style



# **FEATURES**

Provides an efficient bolting surface for grounding and power applications

Electrolytic grade copper

For use with nVent ERICO Cadweld type GL connections only

# **SPECIFICATIONS**

Table 1/3								
Catalog Number	Article Number	Material	Finish	Туре	Height (H)	Length (L)		
B121CE	183650	Copper	Tinned	NEMA®	11.18 mm	36.58mm		


Table 2/3							
Catalog Number	Article Number	Width (W)	Thickness (T)	A	Hole Size (HS)	Angle (a)	
B121CE	183650	25.4 mm	3.18 mm	15.9 mm	14.29 mm	90 °	

Table 3/3					
Catalog Number	Article Number	<b>Equivalent Conductor Size</b>			
B121CE	183650	80.63mm²			

For sizes not listed, contact us.

# **DIAGRAMS**





## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

## Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

## Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

## **APAC**

Shanghai: + 86 21 2412 1618/19 Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSC

ILSCO SCHROFF TRACHTE