

Rail Joint Bond, Signal, C Style



The nVent ERICO Cadweld joint bonds are intended to be welded to the head of the rail profile within the confines of the joint bar. To ensure connection integrity, the attachment shall be made using nVent ERICO Cadweld welding material.

FEATURES

Provides unchanging electrical resistance

Superior corrosion resistance

Easy installation, with minimum installer training required

Simple and highly-portable installation equipment

Equally usable on old, worn, or new rails

Highly durable

SPECIFICATIONS

| Table 1/2 | | | | | | | |
|-------------------|----------------|----------|------------------------|--------------------------------|---------------|---------------|--|
| Catalog Number | Article Number | Material | Bond Terminal Style | Conductor Size | Length 1 (L1) | Length 2 (L2) | |
| CBX3 | 515040 | Copper | С | 50 mm ² Stranded | 175 mm | 30 mm | |

| Table 2/2 | | | | | |
|----------------|----------------|--------------|--|--|--|
| Catalog Number | Article Number | Diameter (Ø) | | | |
| CBX3 | 515040 | 10.5 mm | | | |



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE