

Socket Strip, UTE, Master-Slave, 6 Sockets, 19"

Power Utilities



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with UTE outlets. When the master unit is switched on, the slave outputs are connected to the mains.

CERTIFICATIONS



FEATURES

Connecting cable 2 m, with SCHUKO/UTE plug

Horizontal and vertical mounting

Socket strips can be rotated through all four directions (in 90° increments) during installation

230 V, 16 A

Mounting height 1 U

In accordance with NFC 61-303

When the master unit is switched on, the slave outputs are connected to the mains (switch threshold adjustable)

SPECIFICATIONS

Table 1/1						
Catalog Number	Product Type	Socket Type	Color	Length	Voltage AC	Depth
60110-232	Socket Strip	UTE	Grey	438.5 mm	230 V	44 mm

ADDITIONAL PRODUCT DETAILS

Please order bracket for vertical mounting separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY TRACHTE ERICO HOFFMAN ILSCO SCHROFF