

# MultipacPRO 19" Chassis, Aluminum, for Eurocards Assembly



This 19" chassis is a form of subrack which accepts horizontal board mounting or the mounting of non-standard components like transformers or other heavy load accessories typically mounted on a chassis plate. This version are prepared for horizonatl PCB board assembly.

### **CERTIFICATIONS**



# **FEATURES**

Aluminum construction

Detachable front and rear panel for easy machining

IP 20, in accordance with IEC 60529

Supplied as space-saving flat-pack

Modifications such as cutouts, different finishes or dimensions available

Internal and external dimensions in accordance with: IEC 60297-3-100, -105

EMC shielding: Approx. 20dB(A) at 2 GHz without shielding material. >40dB(A) at 1 GHz with addition of stainless steel gasket between front panel and case body

Cover and base plate drilled with holes for horizontal mounting of euroboards

## **SPECIFICATIONS**

Material: Aluminum

**Finish:** Anodized; Passivated

Product Family: MultipacPRO

EMC Shielding: No (Retrofittable)

Type: Solid

Product Type: Subrack/Chassis

| Table 1/1         |             |       |              |          |  |            |
|-------------------|-------------|-------|--------------|----------|--|------------|
| Catalog<br>Number | Rack Height | Depth | Usable Width | Mounting | Complies With  | Quick Ship |
| 20860-641         | 1U          | 220mm | 403mm        | Rack     | IEC 60297-3-<br>100, IEC 60297-<br>3-101, IEC<br>60297-3-105 | No         |
| 20860-642         | 1U          | 280mm | 403mm        | Rack     | IEC 60297-3-<br>100, IEC 60297-<br>3-101, IEC<br>60297-3-105 | No         |
| 20860-645         | 2U          | 280mm | 403mm        | Rack     | IEC 60297-3-<br>100, IEC 60297-<br>3-101                     | No         |

## ADDITIONAL PRODUCT DETAILS

Please order front handles separately.

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

# **North America**

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

## Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

# Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: nvent.com/schroff

# Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE