

nVent CADDY Rod Lock Nut



FEATURES

Easy "push-to-install" design allows installers to simply push the threaded rod through the mounting hole, instantly holding it in position

Fast installation onto long threaded rods - push the nut in place instead of threading it up the rod


Excellent alignment and easy fine adjustment by spinning the nut


Extremely useful in tight spaces where wrenches are difficult to use

SPECIFICATIONS

Table 1/2							
Catalog Number	Material	Finish	Rod Size (RS)	Height (H)	Width (W)	Wrench Size	
CRLN37EG	Steel	Electrogalvaniz ed	0.375	20 mm	27.3 mm	15/16"	

Table 2/2					
Catalog Number	Torque (TQ)	Static Load			
CRLN37EG	6.8 N·m	6000N			





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO SCHROFF

TRACHTE

