

RackChiller Rear Door Display and Keypad

Data Solutions



The Disply unit allows for local configuration, comissioning and monitoring of the RackChiller Rear Door. It encorporates an LCD panel display and 6 function keys. It installs directly to the cooler's external panel, and connects to the pre-wired cabling within the unit.

CERTIFICATIONS



FEATURES

Monochromatic display 72 x 36 mm, 132x64 pixel

6 function keys allow for direct access to alarms, info, and configuration menus

SPECIFICATIONS

Product Type: Display/Operator Panel

Table 1/1						
Catalog Number	Туре	Package Quantity	Depth	Height	Product Family	Width
23130-599	Passive	1	30.16mm	81.5mm	RackChiller	156mm
23130-621	Active	1	26.21mm	78.9mm	RackChiller	153.4mm

ADDITIONAL PRODUCT DETAILS

RackChiller Rear Door Controller required. This is included in the Active version, please use 21130-594 for Passive version.

For trouble-free operation it is recommended to use the water connection set and the optional accessories.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE