We connect and protect

Thermostat Kit, BPT

The thermostat limits the flow of compressed air, in order for it to be used in situations when cooling is really needed. This saves compressed air, which reduces the operating costs.

FEATURES

Description: Brass solenoid valve and thermostat that limit the flow of compressed air to only when cooling is needed. The thermostat is factory set at 35 °C, but adjustable to any other temperature. The thermostat mounts in a 22 mm diameter hole, and it may be mounted through the enclosure wall or on a bracket inside the enclosure. The thermostatically controlled vortex cooler saves compressed air, and it is recommended where heat load fluctuates and continual purge is not required.

Voltage: 240 V and 50 Hz. Other voltages on request.

Delivery: Thermostat with mounting bracket, and solenoid valve.

This is particular important when mounting a vortex cooler due to the high operating costs to compress air

Brass solenoid valve and thermostat that limit the flow of compressed air to only when cooling is needed

The thermostat is factory set at 35 °C, but adjustable to any other temperature

The thermostat mounts in a 22 mm diameter hole, and it may be mounted through the enclosure wall or on a bracket inside the enclosure

The thermostatically controlled vortex cooler saves compressed air, and it is recommended where heat load fluctuates and continual purge is not required

Voltage: 240 V and 50 Hz. Other voltages on request

Delivery: Thermostat with mounting bracket, and solenoid valve

SPECIFICATIONS

Table 1/1					
Catalog Number	**Enclosure Material**	**Product Family**	**Material**	**Finish**	**Quick Ship**
BPT14	Brass	Climate Control	Brass	Mill	No
BPT38	Brass	Climate Control	Brass	Mill	No

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.