

RayClic Connection Kit

Data Solutions



nVent RAYCHEM RayClic connection system is a simple, fast and reliable set of connection kits developed for select nVent RAYCHEM XL-Trace, IceStop and HWAT self-regulating heating cables. No heat guns or wire stripping are needed, because insulation displacement technology is used to make the electrical connection.

FEATURES

Simple, fast, intuitive connection: no wire stripping or special tools needed

Lower total installed system cost, due to reduced installation time: cold applied, no heat guns or special tools needed

Reliable during long life: 10 year extended product warranty available, maintenance free

Cold applied, no heat guns needed, no special tools

SPECIFICATIONS

Current Rating:	20A
Max Exposure Temperature:	65°C
Voltage Rating:	240V
Connection Type:	Cold Applied
Color:	Grey

Table 1/1

Catalog Number	Article Number	E-Number	Model
636284-000	RAYCLIC-PT-02	9935001670	Power Connection and T-Branch
364855-000	RAYCLIC-S-02	9935001683	Heating Cable/Heating Cable
441524-000	RAYCLIC-T-02	9935001706	T-Branch

Catalog Number	Article Number	E-Number	Model
716976-000	RAYCLIC-PS-02	9935001667	Power Connection to Two Heating Cables
235422-000	RAYCLIC-CE-02	9935001641	Power Connection to One Heating Cable
001013-000	RAYCLIC-X-02	9935001719	X-Branch

ADDITIONAL PRODUCT DETAILS

For proper design and installation of a RayClic connection system, use the appropriate product design guide and the installation instructions included with the connection kit.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE