


# **EuropacPRO EMC Shielding Kit Front/Rear Panel to Horizontal Rail**

# **Power Utilities**



The contact strip clips onto the horizontal rail and makes the contact to front or rear panel.

#### **CERTIFICATIONS**



#### **FEATURES**

The EMC contact strip is clipped onto the horizontal rail and forms a conductive link to front or rear panel

## **SPECIFICATIONS**

| Table 1/2         |            |                     |           |                 |                |               |  |
|-------------------|------------|---------------------|-----------|-----------------|----------------|---------------|--|
| Catalog<br>Number | Rack Width | Package<br>Quantity | Length    | Material        | Product Family | Product Type  |  |
| 24560-231         | 42 HP      | 10                  | 202.9 mm  | Stainless Steel | EuropacPRO     | Shielding Kit |  |
| 24560-235         | 84 HP      | 10                  | 416.56 mm | Stainless Steel | EuropacPRO     | Shielding Kit |  |
| 24560-233         | 63 HP      | 10                  | 304.5 mm  | Stainless Steel | EuropacPRO     | Shielding Kit |  |

| CatalogNumber | Rack Width | Package<br>Quantity | Length    | Material        | Product Family | Product Type  |
|---------------|------------|---------------------|-----------|-----------------|----------------|---------------|
| 24560-229     | 28 HP      | 10                  | 131.78 mm | Stainless Steel | EuropacPRO     | Shielding Kit |
| 24560-236     | 84 HP      | 100                 | 416.56 mm | Stainless Steel | EuropacPRO     | Shielding Kit |

| Table 2/2      |           |            |  |  |  |
|----------------|-----------|------------|--|--|--|
| Catalog Number | Width     | Works With |  |  |  |
| 24560-231      | 202.9 mm  | Subracks   |  |  |  |
| 24560-235      | 416.3 mm  | Subracks   |  |  |  |
| 24560-233      | 304.8 mm  | Subracks   |  |  |  |
| 24560-229      | 131.78 mm | Subracks   |  |  |  |
| 24560-236      | 416.3 mm  | Subracks   |  |  |  |

### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN SCHROFF TRACHTE ILSCO**