

FroStop Self-Regulating Heating Cable



nVent RAYCHEM Frostop self-regulating trace heating cables provide energy efficient and easy to use solutions for pipe freeze protection and and roof and gutter de-icing.

FEATURES

Simple to design

Easy to install: cut to length, meter marks

Energy efficient and safe: self-regulating cable, advanced energy saving controls, no overheating possible

Reliable during long life: 10 year product warranty available, maintenance free

SPECIFICATIONS

Table 1/4						
Catalog Number	Item Name	E-Number	Supply Voltage	Nominal Voltage	Nominal Power Output @ 5°C, 230V	Outer Jacket Material
559303-000	FROSTOP- BLACK- RANDOM	9935000914	220 – 240 V	220 V, 230 V, 240 V	18 W/m	Modified Polyolefin

Table 2/4						
Catalog Number	Item Name	E-Number	Max Circuit Length	Color	Nominal Width	Nominal Height
559303-000	FROSTOP- BLACK- RANDOM	9935000914	80 m	Black	10.5 mm	5.5 mm

Table 3/4						
Catalog Number	Item Name	E-Number	Ground Path Type	Min Installation Temperature	Conductor Material	Min Bending Radius

559303-000	FROSTOP- BLACK- RANDOM	9935000914	Braid	-18 °C	Nickel-Plated Copper	10 mm
------------	------------------------------	------------	-------	--------	-------------------------	-------

Table 4/4							
Catalog Number	er Item Name E-Number Nominal TI						
559303-000	FROSTOP-BLACK-RANDOM	9935000914	5.5 mm				

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com