

nVent CADDY Rod Lock Bottom-Mount Duct Bracket



CERTIFICATIONS



FEATURES

Ideal for modular assembly - allows attachment of brackets to sections of duct while safely on the ground

Slotted holes in bracket allow for horizontal adjustment of the bracket relative to the duct

Easy "push-to-install" design allows installers to simply push the threaded rod through the mounting hole, instantly holding it in position

Ready to use out of the box and eliminates the need for cutting and preparing sections of strut, angle iron, or strap

Integrated adjustment nut enables fine tuning the system height up or down

Lock nut can be finger tightened, locking the rod in place

Extremely useful in tight spaces where wrenches are difficult to use

Includes self-tapping sheet metal screws to attach bracket to duct


SPECIFICATIONS


Table 1/2							
Catalog Number	Material	Finish	Rod Size (RS)	Height (H)	Length (L)	Width (W)	

CRLD37BEG	Steel	Electrogalvaniz ed	0.375	43.18 mm	88.9mm	101.6 mm
-----------	-------	-----------------------	-------	----------	--------	----------

Table 2/2							
Catalog Number	A	Static Load					
CRLD37BEG	63.5 mm	2890N					

DIAGRAMS





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY E

ERICO

HOFFMAN

ILSCO SCHROFF

TRACHTE



©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.