

# Seismic Lighting Fixture Clamp

## Data Solutions



### CERTIFICATIONS

---



### FEATURES

---

Secures fluorescent light fixtures to the ceiling frame members

Requires no additional chains, cables or slack wires attached to the fixture

Helps strengthen integrity of the T-Grid system

Holds in place against the force of standard fire-hose pressure

Meets U.S. building code and electrical code specifications

Also satisfies NEC® 410.16(C) positive attachment for secure fastening of luminaires (fixtures) complying with Building Code Reference AC184

Reusable and cost effective

### SPECIFICATIONS

---

**Finish:** Plain

**Material:** Steel

Table 1/1

Catalog Number	Article Number	Fixture Configuration
SFCLTCF	402245	One 0.61 x 0.61 m Fixture
SFCLT		One Standard Tapered 0.61 x 1.22 m Fixture
SFCLTS		Two Standard Tapered 0.61 x 1.22 m Fixtures Side-by-Side
SFCLTE		Two Standard Tapered 0.61 x 1.22 m Fixtures Side-by-Side
SFCLTCFS		Reinforcement of T-Bar Main Runner/Cross Runner Connections

## ADDITIONAL PRODUCT DETAILS

---

Tested for compliance to the UBC, NEC®, NBC, and CEC.

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**