We connect and protect

# HFBT nVent ERIFLEX Flexibar Bending Tool

## CERTIFICATIONS

RoHS

## FEATURES

- Allows the user to bend nVent ERIFLEX Flexibar into custom shapes for an efficient installation
- Easy-to-use tool bends all sizes of nVent ERIFLEX Flexibar quickly without damage to the insulation
- Portable tool can be used on the jobsite or attached to a workbench
- Includes tool box

## SPECIFICATIONS

Table 1/2

| Catalog Number | Article Number | Material | Bending Radius | Bending Angle | Depth | Height |
|---|---|---|---|---|---|---|
| HFBT | 558920 | Steel | 10mm | 180 ° Max | 120mm | 215 mm |

Table 2/2

| Catalog Number | Article Number | Width | Unit Weight |
|---|---|---|---|
| HFBT | 558920 | 345 mm | 7 kg |

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.


**North America**
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

**Europe**
Netherlands:
+31 800-0200135
France:
+33 800 901 793

**Europe**
Germany:
800 1890272
Other Countries:
+31 13 5835404

**APAC**
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500


Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**


©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.