

Plinth Combining Profiles, PCP



This profile acts as a stabiliser and allows cables to be routed between bayed enclosures, creating the ideal solution when cables have to be installed underneath the enclosure.

FEATURES

Description: Acts as a stabiliser when cabling is routed between bayed enclosures. With the PCP, plinths can be combined and fixed to the floor before the enclosures are mounted on them. The PCP can be used when cables have to go under the enclosure. For 200 mm high plinths, the PCP can be mounted in three different heights, top, middle or bottom. The hole pattern for cage nuts and M5 x 10 screws, allows accessories to be mounted.

Material: 2 mm steel plate.

Finish: RAL 7022 structured powder coating.

Pack quantity: 2 profiles with mounting accessories.

SPECIFICATIONS

Thickness: 2mm

Material: Mild Steel

Finish: Powder Coated

Color Code: RAL 7022 **Color:** Umbra Gray

| Table 1/1 | | | | | | |
|----------------|--------|-------|--------|-----------------------|----------------|------------|
| Catalog Number | Height | Width | Depth | Enclosure Material | Product Family | Quick Ship |
| PCP04 | 60mm | 62mm | 400mm | Mild Steel | Free-Standing | No |
| PCP05 | 60mm | 62mm | 500mm | Mild Steel | Free-Standing | No |
| PCP06 | 60mm | 62mm | 600mm | Mild Steel | Free-Standing | No |
| PCP08 | 60mm | 62mm | 800mm | Mild Steel | Free-Standing | No |
| PCP10 | 60mm | 61mm | 1000mm | Mild Steel | Free-Standing | No |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE