nVent LENTON

We connect and protect

Reinforcing Steel Cleaning Brush

The reinforcing steel cleaning brush is used to prepare reinforcing steel for use with nVent LENTON Cadweld. The brush is designed to remove rust, mill scale, dirt and paint in as little as five seconds.

FEATURES

- Designed for use with a 3/4", heavy duty, low-speed drill (200-350 rpm)
- Cleans reinforcing steel bar, including the bar end

SPECIFICATIONS

Material: Steel

Table 1/1

Catalog Number	Rebar Size, Metric	Rebar Size, US	Rebar Size, Canada	Diameter (Ø)	Length (L)
RBW34311	36 mm	#11	35M	114 mm	244mm
RBW34318	57 mm	#18	55M	127 mm	206mm
RBW34314	43 mm	#14	45M	127 mm	181mm

ADDITIONAL PRODUCT DETAILS

Prior to installation, please read and understand all of the detailed instructions and safety notices provided in the nVent LENTON Cadweld Rebar Splicing System instruction manual.

Brushes must be kept free of grease, oil and other contaminants that could evolve gas and cause porosity in the filler material.

Do not reverse the cleaning brush while it is engaged with the reinforcing steel bar.

Eye protection should be used when using power-driven cleaning brushes.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.