

# **Labrack 19" Open Rack Uprights**



19" uprights for open or bare rack with up to 200 kg load capacity. These 19" uprights can be mounted on a mobile or stationary base.

## **CERTIFICATIONS**



## **FEATURES**

Mobile or stationary

Various shelves

Accessories for cable ducting

Stationary load-carrying capacity 200 kg or 150 kg (see specification table) at a defined center of gravity in the center of the lab rack

Recommended max. chassis depth 400 mm

## **SPECIFICATIONS**

Width: 600mm
Product Type: Rack

| Table 1/2         |             |        |                |                     |                     |               |
|-------------------|-------------|--------|----------------|---------------------|---------------------|---------------|
| Catalog<br>Number | Rack Height | Height | Frame Material | Package<br>Quantity | Complies With       | Finish        |
| 20118-741         | 24U         | 1164mm | Steel          | 1                   | IEC 60297-3-<br>100 | Powder Coated |

| CatalogNumber | Rack Height | Height | Frame Material | Package<br>Quantity | Complies With | Finish        |  |
|---------------|-------------|--------|----------------|---------------------|---------------|---------------|--|
| 20118-742     | 39U         | 1831mm | Steel          | 1                   | IEC 60297-3-  | Powder Coated |  |

| Table 2/2      |          |             |            |  |  |  |
|----------------|----------|-------------|------------|--|--|--|
| Catalog Number | Material | Static Load | Quick Ship |  |  |  |
| 20118-741      | Steel    | 150kg       | No         |  |  |  |
| 20118-742      | Steel    | 150kg       | No         |  |  |  |

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

# Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

## Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

## Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE