

Elbow 45-Degree Lay-in Painted



Lay-in Painted 45-Degree Elbows are used for continuous run with 45-degree turns. Top and inside covers removable so wires and cables can be laid in along wireway run. No pulling through of wires or cables prevents damage to insulation that often occurs in a pull-through wiring system.

FEATURES

Lay-in Painted 45-Degree Elbows are used for continuous run with 45-degree turns

Top and inside covers removable so wires and cables can be laid in along wireway run

No pulling through of wires or cables prevents damage to insulation that often occurs in a pull-through wiring system

SPECIFICATIONS

Color Code: ANSI 61
Color: Gray
Material: Mild Steel
Finish: Powder Coated

| Table 1/1 | | | | | | |
|----------------|----------------|-------|--------|-------|-----------|------------|
| Catalog Number | Article Number | Туре | Height | Width | Thickness | Quick Ship |
| F22G45E | 52080 | Elbow | 64mm | 64mm | 1.52mm | No |
| F1010G45E | 45690 | Elbow | 254mm | 254mm | 1.9mm | No |
| F1212G45E | 51910 | Elbow | 305mm | 305mm | 1.9mm | No |
| F33G45E | 15487 | Elbow | 76mm | 76mm | 1.52mm | No |
| F44G45E | 52240 | Elbow | 102mm | 102mm | 1.52mm | No |
| F66G45E | 52410 | Elbow | 152mm | 152mm | 1.52mm | No |
| F88G45E | 52670 | Elbow | 203mm | 203mm | 1.9mm | No |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE