

Interscale 19" Rack Mount Chassis, Non- Perforated

Power Utilities



Flexible 19" Chassis with integrated EMC protection. Based on the nVent SCHROFF Interscale platform and developed in accordance with IEC 60297-3-109.

CERTIFICATIONS



FEATURES

Modular desktop case consisting of 4 assembled parts

Developed according to IEC 60297-3-109 (under progress at IEC)

Integrated EMC protection

Ingress protection up to IP 30

Color RAL 7016

Modified or customized cases avaiilable upon request

SPECIFICATIONS

Table 1/2						
Catalog Number	Rack Height	Depth	Package Quantity	Usable Width	Mounting	Complies With

14821-105	1 U	221.45 mm	1	443.7 mm	Rack	IEC 60297-3- 100, IEC 60297- 3-109
14821-107	1 U	310.35 mm	1	443.7 mm	Rack	IEC 60297-3- 100, IEC 60297- 3-109
14821-305	3 U	221.45 mm	1	443.7 mm	Rack	IEC 60297-3- 100, IEC 60297- 3-109
14821-205	2 U	221.45 mm	1	443.7 mm	Rack	IEC 60297-3- 100, IEC 60297- 3-109
14821-207	2 U	310.35 mm	1	443.7 mm	Rack	IEC 60297-3- 100, IEC 60297- 3-109
14821-307	3 U	310.35 mm	1	443.7 mm	Rack	IEC 60297-3- 100, IEC 60297- 3-109

Table 2/2						
Catalog Number	EMC Shielding	Product Family	Product Type	Туре		
14821-105	Yes	Interscale	Small Form Factor Case	Solid		
14821-107	Yes	Interscale	Small Form Factor Case	Solid		
14821-305	Yes	Interscale	Small Form Factor Case	Solid		
14821-205	Yes	Interscale	Small Form Factor Case	Solid		
14821-207	Yes	Interscale	Small Form Factor Case	Solid		
14821-307	Yes	Interscale	Small Form Factor Case	Solid		

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**