

# Telescopic Slide Universal, 1 U

Universal Telescopic Slide with > 100 % extension and up to 39 kg load capacity.



#### **CERTIFICATIONS**



#### **FEATURES**

Lateral mounting on the 19" uprights (19" plane remains free for fixing the extension/drawer)

Static load-carrying capacity per pair 23 - 39 kg

Can be removed

Extension length > 100 %

Rail width k = 9.7 mm, max. installation width of extension/drawer w = 429 mm

#### **SPECIFICATIONS**

Material: Steel

Product Type: Telescopic Slide
Finish: Zinc Plated

Table 1/1								
Catalog Number	Length	Package Quantity	Static Load	Туре	Quick Ship			
20110-090	356mm	2	39kg	Universal	No			

Catalog Number	Length	Package Quantity	Static Load	Туре	Quick Ship
20110-091	406mm	2	36kg	Universal	No
20110-092	457mm	2	34kg	Universal	No
20110-093	508mm	2	32kg	Universal	No
20110-094	559mm	2	29kg	Universal	No
20110-095	610mm	2	27kg	Universal	No
20110-096	660mm	2	23kg	Universal	No
20110-097	711mm	2	23kg	Universal	No

## ADDITIONAL PRODUCT DETAILS

Universal telescopic Rails can also be fitted without additional components in non-standard applications, this also in other than 19" cabinets.

To mount on 19" plane please order assembly kit separately.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misused misused products are observed to completely follow nVent's instructions and warnings may equal to the completely follow nVent's instructions and warnings may equal to the completely follow nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions and warnings may equal to the completely follows nVent's instructions are completely follows nVent's instructions and the completely follows nVent's instructions are completely follows nVent's not completely follows nVent's not completely follows nVent's not completely follows nVent's not completel

### **North America**

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

# Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

#### Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: nvent.com/schroff

## Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE