

Fusion G7 Front and Back Vertical Accessory Mounting Rail



Constructed of galvanized steel. Front rail is 2.0-mm thick (14 gauge) and back rail is 1.5-mm thick (16 gauge). Package includes two front and two back rails and mounting screws. Required for side-mount and adjustable-depth accessory installation.

FEATURES

Front rail is 2.0-mm thick (14 gauge) and back rail is 1.5-mm thick (16 gauge)

Package includes two front and two back rails and mounting screws

SPECIFICATIONS

| Table 1/1 | | | | | |
|----------------|------------|------------|-----------|-----------------------|------------|
| Catalog Number | Material | Finish | Thickness | Fits Enclosure Height | Quick Ship |
| FUGS1000G051S | Mild Steel | Galvanized | 2mm | 1000mm | No |
| FUGS1200G051S | Mild Steel | Galvanized | 2mm | 1200mm | No |
| FUGS1500G051S | Mild Steel | Galvanized | 2mm | 1500mm | No |
| FUGS3000G051S | Mild Steel | Galvanized | 2mm | 300mm | No |
| FUGS4000G051S | Mild Steel | Galvanized | 2mm | 400mm | No |
| FUGS5000G051S | Mild Steel | Galvanized | 2mm | 500mm | No |
| FUGS6000G051S | Mild Steel | Galvanized | 2mm | 600mm | No |
| FUGS7000G051S | Mild Steel | Galvanized | 2mm | 700mm | No |
| FUGS8000G051S | Mild Steel | Galvanized | 2mm | 800mm | No |

ADDITIONAL PRODUCT DETAILS

Required for side-mount and adjustable-depth accessory installation.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**