

19" Fan Unit, 1 U, Speed Control and Monitoring

Fan Unit for installation into a 1 U space within the Cabinet.



CERTIFICATIONS



FEATURES

Range selectable: 20 ... 40 °C and 30 ... 50 °C

Low noise through temperature dependent air flow

External sensor, max speed is default failure state

Function control with LEDs and via dry contact

Contact protection in accordance with DIN EN ISO 13857

SPECIFICATIONS

| Table 1/2 | | | | | | | |
|-------------------|---------------------|---------------------|---------------------|--------------------------------------|--------------------|----------------|--|
| Catalog Number | Input Voltage AC | Input Voltage DC | Package Quantity | Finish | Material | Certifications | |
| 10713-098 | | 24V min | 1 | Aluminum-Zinc Plated, Anodized | Steel, Aluminum | CE, RoHS, EAC | |
| 10713-099 | | 24V min | 1 | Aluminum-Zinc Plated, Anodized | Steel, Aluminum | EAC, CE, RoHS | |

| CatalogNumber | Input Voltage AC | Input Voltage DC | Package Quantity | Finish | Material | Certifications |
|---------------|---------------------|---------------------|---------------------|--------------------------------------|--------------------|----------------|
| 19713-006 | 230V | | 1 | Aluminum-Zinc Plated, Anodized | Steel, Aluminum | EAC, RoHS, CE |
| 19713-121 | 230V | | 1 | Aluminum-Zinc Plated, Anodized | Steel, Aluminum | RoHS, EAC |

| Table 2/2 | | | | |
|----------------|------------|--|--|--|
| Catalog Number | Quick Ship | | | |
| 10713-098 | No | | | |
| 10713-099 | No | | | |
| 19713-006 | No | | | |
| 19713-121 | No | | | |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations +1.763.422.2661 Chat with us: nvent.com/schroff

Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: nvent.com/schroff

Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE