

# Through Roof PVC Assembly, Parallel Conductor to In-Line Conductor



#### **CERTIFICATIONS**





## **FEATURES**

Allows for lightning protection conductors to be concealed in ceiling or walls

Use in-line connection for conductor and secure to structure using base plate

## **SPECIFICATIONS**

Conductor Size, UL: Class 1 - Class 2 (4/0 Max)


Table 1/1									
Catalog Number	Material	Connection Material, In- Line Conductor	Connection Material, Parallel Conductor	Rod Length (L)	Outer Diameter (OD)	Unit Weight			
LPC66524	Copper, Polyvinylchlorid e, Stainless Steel 18-8 (EN 1.4305)	Copper	Copper	660.4mm	48.26 mm	1.45 kg			

CatalogNumber	Material	Connection Material, In- Line Conductor	Connection Material, Parallel Conductor	Rod Length (L)	Outer Diameter (OD)	Unit Weight
LPC66524BI	Aluminum, Copper, Polyvinylchlorid e, Stainless Steel 18-8 (EN 1.4305)	Copper	Bi-Metallic	660.4mm	48.26 mm	1.45 kg
LPC66518BI	Aluminum, Copper, Polyvinylchlorid e, Stainless Steel 18-8 (EN 1.4305)	Copper	Bi-Metallic	508mm	48.26 mm	1.25 kg
LPC66518	Copper, Polyvinylchlorid e, Stainless Steel 18-8 (EN 1.4305)	Copper	Copper	508mm	48.26 mm	1.26 kg

## **ADDITIONAL PRODUCT DETAILS**

Always consult the roof manufacturer or owner for proper flashing materials.

# **DIAGRAMS**



## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

 $^{\triangle}$  WARNING: This product can expose you to chemicals including vinyl chloride, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### **North America**

+1.800.753.9221 Option 1 - Customer Care Option 2 - Technical Support

## Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

#### **Europe**

Germany: 800 1890272 Other Countries: +31 13 5835404

#### **APAC**

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN TRACHTE ILSCO SCHROFF**