

HRD Snow Sensor



nVent RAYCHEM HRD Snow Sensor accurately detects falling or blowing snow as precipitation at temperatures below 38 °F/3.3 °C for surface snow melting applications. Typically the CIT-1 aerial sensor is paired with either the GIT-1 sensor for gutter applications or the SIT-6E sensor for pavement applications.

FEATURES

Simple and fast to install

Excellent snow detection accuracy, using precision precipitation and temperature sensors

Aerial snow sensor detects falling or blowing precipitation before snow or ice begin to accumulate

No ice bridging, due to the unique microcontroller design

Remote use, with up to 2000 ft/609.6 m separation from the control panel possible

Reliable during long life: 10 year product warranty available, maintenance free

SPECIFICATIONS

| Table 1/2 | | | | | | | |
|-------------------|---------------------------------|----------------|-----------|-------------|---------|----------|--|
| Catalog Number | Item Name | Supply Voltage | IP Rating | Sensor Type | Height | Width | |
| 126795-000 | HRD-GIT-1- GUTTER- SENSOR | 24 V | IP67 | Gutter | 38.1 mm | 141.2 mm | |

| Table 2/2 | | | | | |
|----------------|------------------------------------|-------|--|--|--|
| Catalog Number | Item Name | Depth | | | |
| 126795-000 | 795-000 HRD-GIT-1-GUTTER-SENSOR | | | | |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com **Latin America**

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com