

TT-TS12 Alarm Panel



nVent RAYCHEM TraceTek TT-TS12 Touch Screen Panel provides a graphic user interface to manage and display information from a network of up to 250 external leak detection circuits. With interactive and dynamic leak location maps and displays, the leak location can be displayed on the floor plan, piping layout or photo of a single piece of equipment. Provides a quick status overview of all leak detection cables. Works with TTSIM or wireless mesh transmitters.

FEATURES

Easy to install, simple to set up and operate

Graphic display of leak location: 12" full color, high resolution SVGA touch screen display

Flexible interface options: audible alarm, summary relays, serial data and web interfaces are provided as standard

Onboard memory for up to 5000 events, simple off-line archiving and software updates

Available in various configurations

Email alerts allow 24/7 remote notification of an alarm

CE and UL 508 compliant

SPECIFICATIONS

Relay Contacts: 8 Relays (4 System, 4 User Programmable)

Display: 12" Touch Screen, TFT LCD

Depth:54 mmHeight:237 mmWidth:311 mmOperating Temperature:-20 to 60 °C

Table 1/1			
Catalog Number	Item Name	Number of TTSIM	
P000001487	TT-TS12-PANEL-S1-1	1 x TTSIM-1	
P000001491	TT-TS12-PANEL-S1A-1	1 x TTSIM-1A	

Catalog Number	Item Name	Number of TTSIM
P000001488	TT-TS12-PANEL-S1-2	2 x TTSIM-1
P000001492	TT-TS12-PANEL-S1A-2	2 x TTSIM-1A
P000001493	TT-TS12-PANEL-S1A-3	3 x TTSIM-1A
P000001489	TT-TS12-PANEL-S1-3	3 x TTSIM-1
P000001494	TT-TS12-PANEL-S1A-4	4 x TTSIM-1A
P000001490	TT-TS12-PANEL-S1-4	4 x TTSIM-1
P000001486	TT-TS12-PANEL-0	No

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa Tel +32.16.213.511

Fax +32.16.213.604 thermal.info@nvent.com **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com