





NVENT THERMAL MANAGEMENT
7433 HARWIN DRIVE
HOUSTON, TX 77036
TOLL FREE: 1-800-545-6258
PHONE: (650) 216-1526
FAX: (800) 527-5703
www.raychem.nvent.com



NOTES:

1. ALL CONNECTIONS MUST BE MADE OFF THE PIPE.
2. FLUOROPOLYMER (-CT) JACKET REQUIRED FOR GREASY WASTE APPLICATION.
3. RAYCLIC-PC AND FTC-XC POWER CONNECTION KITS INCLUDE RAYCLIC-E END SEAL.
4. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
5. DO NOT SCALE DRAWING.
6. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
7. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
8. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 3408-054.



BURIED PIPE FREEZE PROTECTION

TYPICAL UNDERGROUND PIPING INSTALLATION DETAIL