

Aisle Containment Automatic Top Cover

Data Solutions



Top cover that can be automatically opened in case of an event on site.

CERTIFICATIONS



FEATURES

Automatic containment top covers open automatically in the event of fire so that the facility sprinkler systems can put out the fire. In normal operation, the top covers are kept closed by electromagnets and open when the floating contact of the fire detection system is opened

Suitable for an aisle width of 1200 mm

Top cover with safety glass, 7 mm

With the universal top cover profile, the aisle height can be increased by 84 mm; please order separately

The top cover can be removed from the inside. When opened, the top cover provides access to lighting and sprinkler systems above the containment system for maintenance work

Please order the control unit, which can be used to control up to 12 automatic top covers, separately

A 24 VDC power supply unit is required to operate the system. Please order separately

SPECIFICATIONS

Table 1/2						
Catalog Number	Width	Depth	Package Quantity	Color	Color Code	Finish

2	21130-592	600mm	1200mm	1	Black Grey	RAL 7021	Powder Coated

Table 2/2							
Catalog Number	Material	Product Type	Туре	Works With			
21130-592	Steel, Glass	Cover	Aisle Top Cover, Automatic	Aisle Containment			

ADDITIONAL PRODUCT DETAILS

Please order the control unit, which can be used to control up to 12 automatic top covers, separately.

A 24 VDC power supply unit is required to operate the system. Please order separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of

CADDY TRACHTE ERICO HOFFMAN ILSCO SCHROFF

their respective owners. nVent reserves the right to change specifications without notice. nVent.com 2 This document is system-generated.