

Guide Rail Multi Piece, Mid-Piece Aluminium/Plastic Extrusion

Power Utilities

FEATURES

Middle profile for mounting guide rails for 2.5 mm groove width

2 plastic end pieces are required; these are pushed on to both ends of the middle profile

Guide rails can be clipped into horizontal rails (Al extrusion) or into 1.5 mm thick plates

Storage temperature: from -40 °C ... 130 °C

SPECIFICATIONS

Table 1/1						
Catalog Number	Board Depth	Color	Groove Width	Material	Туре	Works With
34562-813	160 mm	Silver	2.5	Aluminium	Middle Section	Subracks, Cases, Chassis
34562-814	220 mm	Silver	2.5	Aluminium	Middle Section	Subracks, Cases, Chassis
34562-815	280 mm	Silver	2.5	Aluminium	Middle Section	Subracks, Cases, Chassis
34562-816	340 mm	Silver	2.5	Aluminium	Middle Section	Subracks, Cases, Chassis
34562-822	1000 mm	Silver	2.5	Aluminium	Middle Section	Subracks, Cases, Chassis

ADDITIONAL PRODUCT DETAILS

Delivery may be in Standard Pack Quantity (SPQ). Pricing is per individual item.

One guide rail consists of 1 pair of head pieces and 1 profile piece.

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE