

# **Polymer Junction Box For MI Cables**



nVent RAYCHEM JB-EX-xx-EP are a range of polymer junction boxes with an integrated earth plate for use in hazardous areas with mineral insulated (MI) heating cables. They are designed considering space constraints to allow easy connections of MI heating units equipped with M25 glands to a power supply or other configurations such as tees or splices. Earthing is realized through the earth plate. Available in different sizes and amounts of entries to accommodate various configurations and electrical loads.

## **FEATURES**

Simple and fast to install, easy to maintain

Hazardous area approved

Advanced design ensures that various configurations with MI heating units are possible

Reliable during long life: 10 year product warranty available, maintenance free

# **SPECIFICATIONS**

**Area Classification:** Non-Hazardous; Hazardous

**IP Rating:** IP66

**Mounting:** Wall/Support Bracket Mounted

Ambient Temperature: -55 to 55 °C

Table 1/2								
Catalog Number	Item Name	Max Voltage	Cable Entry	Max Conductor Cross Section	Height	Width		
1244-020505	JB-EX-40-EP	550 V	1xM25 3xM25	10 mm²	160 mm	160 mm		
1244-020506	JB-EX-41-EP	550 V	1xM25 6xM25	10 mm²	160 mm	160 mm		
1244-020507	JB-EX-42-EP	690 V	1xM40 6xM25	35 mm²	160 mm	260 mm		

Table 2/2								
Catalog Number	Item Name	Depth	Light Indication Included	Earth Plate Included				
1244-020505	JB-EX-40-EP	90 mm	No	Yes				
1244-020506	JB-EX-41-EP	90 mm	No	Yes				
1244-020507	JB-EX-42-EP	90 mm	No	Yes				

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com