

## CleanTray 45-Degree Elbow



Clean Tray 45-Degree Elbows are used for continuous runs with 45-degree turns. The Clean Tray stainless steel system is designed to protect rated cabling in applications that require frequent washdown.

## **FEATURES**

Clean Tray 45-Degree Elbows are used for continuous runs with 45-degree turns

The Clean Tray stainless steel system is designed to protect rated cabling in applications that require frequent washdown

## **SPECIFICATIONS**

Finish: Brushed #3

Stainless Steel 304 Material:

Table 1/1								
Catalog Number	Туре	Height	Width	Thickness	Quick Ship			
CT22EFC45SS	Elbow	51mm	51mm	1.27mm	No			
CT33EFC45SS	Elbow	76mm	76mm	1.27mm	No			
CT33EIC45SS	Elbow	76mm	76mm	1.27mm	No			
CT33EOC45SS	Elbow	76mm	76mm	1.27mm	No			
CT44EFC45SS	Elbow	102mm	102mm	1.27mm	No			
CT44EIC45SS	Elbow	102mm	102mm	1.27mm	No			
CT44E0C45SS	Elbow	102mm	102mm	1.27mm	No			
CT44PEFC45SS	Elbow	102mm	102mm	1.27mm	No			
CT46EFC45SS	Elbow	102mm	152mm	1.27mm	No			
CT46EIC45SS	Elbow	102mm	152mm	1.27mm	No			
CT46EOC45SS	Elbow	102mm	152mm	1.27mm	No			
CT66EFC45SS	Elbow	152mm	152mm	1.27mm	No			
CT66EOC45SS	Elbow	152mm	152mm	1.27mm	No			
CTS33EFC45SS	Elbow	76mm	76mm	1.27mm	No			
CTS33PEFC45SS	Elbow	76mm	76mm	1.27mm	No			
CTS44EFC45SS	Elbow	102mm	102mm	1.27mm	No			
CTS44PEFC45SS	Elbow	102mm	102mm	1.27mm	No			

Catalog Number	Туре	Height	Width	Thickness	Quick Ship
CTS46EFC45SS	Elbow	102mm	152mm	1.27mm	No
CTS46PEFC45SS	Elbow	102mm	152mm	1.27mm	No
CTS66EFC45SS	Elbow	152mm	152mm	1.27mm	No
CTS66PEFC45SS	Elbow	152mm	152mm	1.27mm	No
CT22EIC45SS	Elbow	51mm	51mm	1.27mm	No
CT22EOC45SS	Elbow	51mm	51mm	1.27mm	No
CT22PEFC45SS	Elbow	51mm	51mm	1.27mm	No
CT33PEFC45SS	Elbow	76mm	76mm	1.27mm	No
CT46PEFC45SS	Elbow	102mm	152mm	1.27mm	No
CT66EIC45SS	Elbow	152mm	152mm	1.27mm	No
CT66PEFC45SS	Elbow	152mm	152mm	1.27mm	No

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY **ERICO HOFFMAN TRACHTE SCHROFF ILSCO**