

# IceStop Self-Regulating Cable Kit



nVent RAYCHEM IceStop self-regulating trace heating cable kits provide roof and gutter de-icing, suitable for all standard materials of gutters and drainpipes. Power output is 36 W/m at 0 °C in ice water, 18 W/m at 0 °C in air.

## **FEATURES**

Simple to design

Easy to install, pre-terminated kits: 5 - 30 m, each with 8 m power cable, GM-RAKE fixing bracket and RayClic end seal

Safe and efficient in operation: no overheating, even when crossed, advanced energy saving controls

Reliable during long life: 10 year extended product warranty available, maintenance free

## **SPECIFICATIONS**

**Nominal Height:** 6 mm **Cold Lead Length:** 8 m **Nominal Width:** 14 mm Nominal Power Output, In Air @ 0°C, 230V: 18 W/m Nominal Power Output, In Ice Water @ 0°C, 230V: 36 W/m 65°C Max Continuous Exposure Temperature, Power On: 85 °C Max Intermittent Exposure Temperature, Power On: **Nominal Cable Weight:** 120 g/m 220 - 240 V Supply Voltage: **Max Cumulative Hours for Intermittent Exposure:** 800 h -18 °C Min Installation Temperature: Color: Black **Ground Path Type:** Braid

Outer Jacket Material:Modified PolyolefinHeating Cable Technology:Self-Regulating

Table 1/1			
Catalog Number	Item Name	Length	

106160-000	GM-2X-SA-8	8 m
159067-000	GM-2X-SA-12	12 m
191808-000	GM-2X-SA-5	5 m
650854-000	GM-2X-SA-16	16 m
838627-000	GM-2X-SA-25	25 m
925956-000	GM-2X-SA-30	30 m
973923-000	GM-2X-SA-20	20 m

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com