

Horizontal Rail Rear, Type AB for Rear I/O Board Guides, 28 HP

CATALOG NUMBER

34561-528



Combinations of horizontal rails and side panels

4×4 can be combined. 5×5 combination not recommended.

Height of P		Subtype 1	Subtype 2	Subtype 3	Subtype 4
Height 2.0		-	Subtype 1: 2.0m high horizontal rail with 4x4 grid	Subtype 2: 2.0m high horizontal rail with 5x5 grid	Subtype 3: 2.0m high horizontal rail with 4x4 grid
Height 2.5		+	Subtype 1: 2.5m high horizontal rail with 4x4 grid	+	+
Height 3.0		Subtype 3: 3.0m high horizontal rail with 4x4 grid	Subtype 2: 3.0m high horizontal rail with 4x4 grid	+	-
Horizontal rail		Subtype 4: 4.0m high horizontal rail with 4x4 grid	Subtype 3: 4.0m high horizontal rail with 4x4 grid	Subtype 2: 4.0m high horizontal rail with 4x4 grid	Subtype 1: 4.0m high horizontal rail with 4x4 grid
Side panel		Subtype 1: 2.0m high side panel with 4x4 grid	Subtype 2: 2.0m high side panel with 5x5 grid	Subtype 3: 2.0m high side panel with 4x4 grid	Subtype 4: 2.0m high side panel with 4x4 grid

Subtype 1 Subtype 2 Subtype 3 Subtype 4

Aluminum extrusion horizontal rail of the type AB (AB = support), for rear I/O card guides, with an anodized surface and conductive contact surface. Suitable for RatiopacPRO/-AIR and EuropacPRO/-rugged).

CERTIFICATIONS



FEATURES

For CompactPCI in the area of rear I/O

For 2×3 U expansion, 2 horizontal rails of type AB are required

Aluminum extrusion, anodized surface, conductive contact surface, without HP markings

PRODUCT ATTRIBUTES

Rack Width: 28HP

Package Quantity: 1

Finish: Anodized

Length: 147.32mm

Material: Aluminum

Product Family: EuropacPRO; RatiopacPRO; RatiopacPRO AIR; CompacPRO; PropacPRO

Product Type: Horizontal Rail

Type: Type AB

Works With: Subracks; Cases

Gross Weight: 0.026kg

ADDITIONAL PRODUCT DETAILS

Delivery is in standard pack multiples. Pricing is per individual item.

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE