

nVent CADDY Speed Link SLS with Wedge Anchor



CERTIFICATIONS





FEATURES

Complete system includes wire, locking device and wedge anchor from Powers Fasteners, Inc.

Quickly and easily attaches into cracked and non-cracked concrete

Installs in strut profiles without the need to insert fingers or tools into the strut

Finger tightening of nut secures the locking device into position without tools

No special tools required

ETA-13/0355 assessment available for wedge anchor from Powers Fasteners, Inc

SPECIFICATIONS

Wire Rope Diameter: 2 mm Static Load Safety Factor: 5:1

Finish: Electrogalvanized

Material: Steel;Polypropylene;Zinc Alloy

Complies With: SMACNA HVAC-DCS

| Table 1/2 | | | | | | | |
|-------------------|----------------|---------------------|------------|-----------------------|------------------|--------------------|--|
| Catalog Number | Article Number | Wire Rope Length | Length (L) | Drill Bit Diameter | Drill Hole Depth | Embedment Depth | |
| SLS2L5WA6 | 196760 | 5m | 63.5mm | 6mm | 60mm | 55 mm Min | |
| SLS2L3WA6 | 196759 | 3m | 63.5mm | 6mm | 60mm | 55 mm Min | |

| Table 2/2 | | | | | |
|----------------|----------------|-------------|--|--|--|
| Catalog Number | Article Number | Static Load | | | |
| SLS2L5WA6 | 196760 | 270N | | | |
| SLS2L3WA6 | 196759 | 270N | | | |

Slot Size (SS): 8 x 6.5 mm - 8 x 10 mm

Hole Size (HS): 8 - 10 mm Width (W): 16 mm Height 2 (H2): 43.5mm Height 1 (H1): 53mm Thread Size (TS): M8


Thickness (T): 4 mm Max

ADDITIONAL PRODUCT DETAILS

The 2 mm locking device is compatible with C-Channel Types E0 and E0L.

Total load per wire on a multi-tier trapeze must not exceed static load.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE



©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.