


EuropacPRO 19" Subrack Kit for Backplane, Shielded, 6 U, 355 mm

CATALOG NUMBER

24563-444



EMC Shielded subrack for backplane mounting, rear side covered by a rear panel.

CERTIFICATIONS



FEATURES

Subrack with side panel type F ("flexible"), front 19" bracket included, depth-adjustable 19" bracket sold separately (not included in items delivered)

Supplied as space-saving flat-pack

Modifications such as cutouts, different finishes or dimensions available

EMC of approximately 40 dB at 1 GHz, 30 dB at 2 GHz, assuming that the front is covered with shielded front panels, testing in accordance with VG 95373 part 15

IP 20, in accordance with IEC 60529

Aluminum construction

Internal and external dimensions in accordance with: IEC 60297-3-100, -101, IEEE 1101.1

Rear horizontal rail for backplane mounting with insulation strip

Horizontal rail type "light"

Rack Height: 6U
Depth (D): 355mm
Package Quantity: 1
For Mounting: Backplane
Board Depth: 160mm; 220mm; 280mm
Gasket Type: Textile EMC
Handle Included: No
Mounting: Rack
Complies With: IEC 60297-3-103
EMC Shielding: Yes
Finish: Anodized; Passivated
Material: Aluminum
Product Type: Subrack/Chassis
Rack Width: 84HP
Static Load: 11kg
Net Weight: 4.34kg

Individual configuration: broad range of variants in height, width and depth; guide rails for a wide variety of applications; interior options; accessories and mounting material.

Exploded view diagram of a 1000mm x 1000mm metal cabinet. The diagram shows the main frame (1), top panel (7), and bottom panel (7). Dimensions are provided for the main frame: 400 x 500mm (1), 400 x 500mm (2), 400 x 500mm (3), 400 x 500mm (4), 400 x 500mm (5), 400 x 500mm (6), 400 x 500mm (7), 400 x 500mm (8), 400 x 500mm (9), 400 x 500mm (10), 400 x 500mm (11), 400 x 500mm (12), 400 x 500mm (13), 400 x 500mm (14), 400 x 500mm (15), 400 x 500mm (16), 400 x 500mm (17), 400 x 500mm (18), 400 x 500mm (19), 400 x 500mm (20), 400 x 500mm (21), 400 x 500mm (22), 400 x 500mm (23), 400 x 500mm (24), 400 x 500mm (25), 400 x 500mm (26), 400 x 500mm (27), 400 x 500mm (28), 400 x 500mm (29), 400 x 500mm (30), 400 x 500mm (31), 400 x 500mm (32), 400 x 500mm (33), 400 x 500mm (34), 400 x 500mm (35), 400 x 500mm (36), 400 x 500mm (37), 400 x 500mm (38), 400 x 500mm (39), 400 x 500mm (40), 400 x 500mm (41), 400 x 500mm (42), 400 x 500mm (43), 400 x 500mm (44), 400 x 500mm (45), 400 x 500mm (46), 400 x 500mm (47), 400 x 500mm (48), 400 x 500mm (49), 400 x 500mm (50), 400 x 500mm (51), 400 x 500mm (52), 400 x 500mm (53), 400 x 500mm (54), 400 x 500mm (55), 400 x 500mm (56), 400 x 500mm (57), 400 x 500mm (58), 400 x 500mm (59), 400 x 500mm (60), 400 x 500mm (61), 400 x 500mm (62), 400 x 500mm (63), 400 x 500mm (64), 400 x 500mm (65), 400 x 500mm (66), 400 x 500mm (67), 400 x 500mm (68), 400 x 500mm (69), 400 x 500mm (70), 400 x 500mm (71), 400 x 500mm (72), 400 x 500mm (73), 400 x 500mm (74), 400 x 500mm (75), 400 x 500mm (76), 400 x 500mm (77), 400 x 500mm (78), 400 x 500mm (79), 400 x 500mm (80), 400 x 500mm (81), 400 x 500mm (82), 400 x 500mm (83), 400 x 500mm (84), 400 x 500mm (85), 400 x 500mm (86), 400 x 500mm (87), 400 x 500mm (88), 400 x 500mm (89), 400 x 500mm (90), 400 x 500mm (91), 400 x 500mm (92), 400 x 500mm (93), 400 x 500mm (94), 400 x 500mm (95), 400 x 500mm (96), 400 x 500mm (97), 400 x 500mm (98), 400 x 500mm (99), 400 x 500mm (100).

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE