

Speedway Cable Ladder Equal Tee



CERTIFICATIONS



FEATURES

Creates a quick and easy equal tee pathway intersection

Provides optimal support for high-performance low voltage and data cables

Innovative SPEEDLOK integrated coupling system

Safety edge protects cables during installation

Slotted side channel, eliminating field drilling for cut-to-length applications

IEC 61537 load rating and earthing compliant

Responsive design and layout services, including seismic

SPECIFICATIONS


Finish: Hot-Dip Galvanized

Material: Steel

Table 1/2						
Catalog Number	Article Number	Width (W)	Angle (a)	A	В	С

CL110X150ETH D	840700	150 mm	90°	900 mm	450 mm	950 mm
CL110X300ETH D	840710	300 mm	90 °	900 mm	525 mm	950 mm
CL110X450ETH D	840720	450 mm	90 °	900 mm	600 mm	950 mm
CL110X600ETH D	840730	600 mm	90 °	900 mm	675 mm	950 mm
CL110X750ETH D	840740	750 mm	90 °	900 mm	750 mm	950 mm
CL110X900ETH D	840750	900 mm	90 °	900 mm	825 mm	950 mm

Table 2/2						
Catalog Number	Article Number	D	E			
CL110X150ETHD	840700	80 mm	110 mm			
CL110X300ETHD	840710	80 mm	110 mm			
CL110X450ETHD	840720	80 mm	110 mm			
CL110X600ETHD	840730	80 mm	110 mm			
CL110X750ETHD	840740	80 mm	110 mm			
CL110X900ETHD	840750	80 mm	110 mm			



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO SCHROFF

TRACHTE

