

Hammer Die



FEATURES

Hardened steel die

Used to form the end of a field-made bond

Formed end designed to fit specific nVent ERICO Cadweld mold

SPECIFICATIONS

Material: Steel

| Table 1/1 | | | | | | |
|----------------|----------------|-----------|--------------------------------|--------------------|--|--|
| Catalog Number | Article Number | Туре | Conductor Size | nVent ERICO Sleeve | | |
| JD05 | | Grounding | 1/0 Concentric | S05F | | |
| WD80 | | Power | 1/0 Concentric | S05F | | |
| WD84 | | Power | 2/0 Concentric, 1/0 Ropelay | S03F | | |
| JD03 | | Grounding | 2/0 Concentric | S03F | | |
| JD06 | | Grounding | 2/0 Ropelay | S06F | | |
| WD85 | | Power | 2/0 Ropelay | S06F | | |

| Catalog Number | Article Number | Туре | Conductor Size | nVent ERICO Sleeve |
|----------------|----------------|-----------|--------------------------------------|--------------------|
| SBD50 | | Signal | 3/16" Bondstrand | SBS12C |
| JD01 | | Grounding | 4/0 Concentric | S01F |
| WD82 | | Power | 95 mm² Concentric, 4/0 Concentric | S01F |
| JD02 | | Grounding | 4/0 Ropelay | S02F |
| WD83 | | Power | 4/0 Ropelay | S02F |
| WD88 | | Power | 4/0 Welding cable | S429F3N16 |
| SBD51 | | Signal | 5/16" Bondstrand | SBS09C |
| SBD55 | | Signal | 35 mm² Concentric | S17F |
| WD94 | | Power | 35 mm² Concentric | S17F |
| PBWD102 | 184200 | Power | 120 mm² Concentric | H106F |
| PBWD104 | | Power | 145 mm² Concentric | S429F3N16 |
| WD87 | | Power | 150 mm² Ropelay | S24F |
| PBWD106 | 184090 | Power | 240 mm² Concentric | S429FY922 |
| WD105 | | Power | 240 mm² Concentric | S429FY922 |
| PBWD99 | | Power | 240 mm² Ropelay | S429F3N16 |
| JD07 | | Grounding | 250 kcmil Ropelay | S07F |
| WD79 | | Power | 500 kcmil Ropelay | S429F3S20 |
| JD09 | | Grounding | #2 Concentric | S09F |

| Catalog Number | Article Number | Туре | Conductor Size | nVent ERICO Sleeve |
|----------------|----------------|-----------|-----------------------|--------------------|
| JD11 | | Grounding | #4 Concentric | S20F |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793 Europe

Germany: 800 1890272 Other Countries: +31 13 5835404 **APAC**

Shanghai: + 86 21 2412 1618/19 Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE