

HRD Snow Sensor



nVent RAYCHEM HRD Snow Sensor accurately detects falling or blowing snow as precipitation at temperatures below 38 °F/3.3 °C for surface snow melting applications. Typically the CIT-1 aerial sensor is paired with either the GIT-1 sensor for gutter applications or the SIT-6E sensor for pavement applications.

FEATURES

Simple and fast to install

Excellent snow detection accuracy, using precision precipitation and temperature sensors

Aerial snow sensor detects falling or blowing precipitation before snow or ice begin to accumulate

No ice bridging, due to the unique microcontroller design

Remote use, with up to 2000 ft/609.6 m separation from the control panel possible

Reliable during long life: 10 year product warranty available, maintenance free

SPECIFICATIONS

Table 1/2

Catalog Number	Item Name	Supply Voltage	IP Rating	Sensor Type	Height	Width
126795-000	HRD-GIT-1-GUTTER-SENSOR	24 V	IP67	Gutter	38.1 mm	141.2 mm

Table 2/2

Catalog Number	Item Name	Depth
126795-000	HRD-GIT-1-GUTTER-SENSOR	38.1 mm

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause

product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nvent.com

**Europe, Middle East,
Africa**

Tel +32.16.213.511
Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nvent.com

Our powerful portfolio of brands:

RAYCHEM PYROTENAX TRACER NUHEAT